



Manufacturer of pneumatic impact tools and hydraulic tools for mines, quarries, construction industry, steelworks and foundries.

TECHNICKÉ ÚDAJE – TECHNISCHE DATEN – TECHNICAL DATA



BKA 25 Breaking Hammer

APPLICATION

The breaking hammer is a versatile tool. It is designed for breaking up low to medium strength rock and material (concrete, bituminous roadways, masonry etc.). Its design and weight favors use in downwards-horizontal or sloping direction.

Technické údaje – Technische data – Technical data	ISO	BKA25A	BKA25B	BKA25C
Váha - Gewicht - Weight	kg		25	
Energie úderu - Schlagenergie - Impact energy	J		65	
Frekvence úderů - Schlagfrequenz - Impact frequency	Hz		24	
Spotřeba vzduchu - Luftverbrauch - Air consumption	m ³ .min ⁻¹		1,7	
Garantovaná hladina akustického výkonu L _{WA} - Garantierter Lärmpegel L _{WA} - Guaranteed noise level L _{WA}	dB		105	
Vážená hodnota vibrací - Vibrationspegel - Vibration level	m.s ⁻²		3,4	
Délka - Länge - Length	mm	659	694	694
Šířka - Breite - Width	mm		441	
Provozní přetlak vzduchu - Betriebsluftdruck - Oper. air pressure	bar		4-7	
Stopka nástroje - Einsteckende - Tool shank	mm	#25x108	#28x160	#32x160
Přívodní hadice - Luftzufuhrschlauch - Air supply hose	mm		Js 13, 16, 20	

www.permon.cz
e-mail : prodej@permon.cz
e-mail : export@permon.cz

Roztoky 217, 270 23 Krivoklát, Česká republika
pro ČR, SR - for the Czech Rep. and SK T: + 420 313 521 567
pro ostatní země - für andere Gebiete - for other territories T: + 420 313 521 563
v : 6.5.2020